

AE5640-K9 Garmin Kit to Ag Leader 2000, 3000, Insight, Edge, Integra

Kit Contents:

AE5640: Garmin Receiver

AE5641: Magnetic Mounting Plate

AE72991: RJ45/DB9 Adapter

Follow these steps when connecting a Garmin receiver kit to an Ag Leader 2000, 3000,
Insight, Edge, Integra

1. Power down the machine and leave the key switch in the off position.
2. Power down the console or display by using the power switch.

2000 & 3000

3. Plug the AE72991 adapter into the Port 1 position on the 3000 or serial port on the 2000 on the bottom of the console.
4. Connect the RJ45 connector from the Garmin receiver to the jack on the AE72991 adapter.
5. Turn the key switch to the on position or power on the machine.
6. Power on the console.
7. The receiver has been preprogrammed to work with this system.
8. GPS position should show within a few minutes of the system being powered. A capital DG will show in the upper right corner of the screen when differential GPS has been acquired.

Insight, Edge, Integra

3. Plug the AE72991 adapter into the GPS connector on the display harness.
4. Connect the RJ45 connector from the Garmin receiver to the jack on the AE72991 adapter.
5. Turn the key switch to the on position or power on the machine.
6. Power on the console.
7. The receiver has been preprogrammed to work with this system.
8. GPS position should show within a few minutes of the system being powered. GPS Diagnostics will show details of the GPS signal and quality.